

DESCRIPTION

Gain visual access through small cracks or openings with the Handheld Inspection Tool 2. Featuring a 9 inch flexible neck and low light camera, the HHIT2 is highly portable and transmits video wirelessly to any Tactical Electronics monitor. This unit allows covert vision and is ideal for looking around corners and inspecting packages.

SPECIFICATIONS

WEIGHT:	0.8 lbs
DIMENSIONS (L X W X H):	20.25in x 2.840in x 1.50in
POWER SUPPLY:	Three 3V Lithium batteries (CR123A type)
RUNTIME:	2.5 hours
HOUSING MATERIAL:	High-density polyethylene (HDPE), anodized aluminum
OPERATING TEMPERATURE RANGE:	-10°C to +50°C, 95% humidity
FREQUENCY RANGE:	2.4 to 2.485 Ghz (4 channel system)
TRANSMISSION DISTANCE:	Up to 400ft line of sight
COMPATIBLE MONITORS:	Wrist Mounted Monitor (WMM) or Handheld Monitor (HMM)
CAMERA RESOLUTION:	600 lines
CAMERA LIGHT SENSITIVITY:	0.0003 lux
CAMERA SENSOR TYPE:	1/3in Sony Super HAD CCD
FIELD OF VIEW:	92 degrees
ILLUMINATION:	2 forward facing variable intensity LEDs, colors available: EOD, IR, Blue, White, Green

KIT CONTENTS

- » One: Handheld Inspection Tool
- » One: Soft sided carry bag

