

**DESCRIPTION**

The Split Shot Scope Transmitter from Tactical Electronics provides operators with integrated mounting to multiple optical scopes. The Split Shot System is uniquely designed to provide the user with real-time wireless video transmission of images and targets viewed directly through the optical scope lens.

SPECIFICATIONS

WEIGHT:	1.242 lbs.
DIMENSIONS (L X W X H):	5.166in x 2.084in x 1.574in
POWER SUPPLY:	Two 3V Lithium batteries (CR123A type)
RUNTIME:	4 hours
OPERATING TEMPERATURE RANGE:	-10°C to +50°C, 95% humidity
FREQUENCY RANGE:	2.4 to 2.485 Ghz (4 channel system)
TRANSMISSION DISTANCE:	Up to 400ft line of sight
COMPATIBLE MONITORS:	Wrist Mounted Monitor (WMM) or Handheld Monitor (HMM)
CAMERA RESOLUTION:	550 TVL
CAMERA LIGHT SENSITIVITY:	0.05 lux
CAMERA SENSOR TYPE:	1/3in Super-HAD CCD

KIT CONTENTS

- » One: Split Shot Scope Transmitter
- » One: Monitoring option (Handheld or Wrist Mounted)
- » One: Soft sided carry bag

