
CORE POLE Grip

SPEC SHEET: TACTICAL ELECTRONICS





DESCRIPTION

 $\overline{\mathbf{v}}$

The CORE POLE Grip is available in multiple sizes: 8ft extended, 10ft extended, 17ft extended, and a Hinged 17ft extended. The CORE Pole Camera, CORE Under Door Camera, and CORE Flex Camera can be attached to the end of these telescoping poles.

Each pole is constructed of high density graphite, features locking extensions, and collapses down to 28in (8ft POLE Grip), 37in (10ft POLE Grip), 47in (17ft POLE Grip), and 35in (17ft Hinged POLE Grip) for easy deployment and stow away.

The LCD status screen provides pertinent information about the attached camera: LED illumination, battery status, camera view, camera name, recording status, date/time, & Wi-Fi pairing information.



CONTACT :

TACTICAL ELECTRONICS P: 833/483/1441 P: 918/249/8326 F: 918/249/8328

WEBSITE : TACTICALELECTRONICS.COM

DOCUMENT : OFFICIAL SPECIFICATIONS SHEET *PROPRIETARY*

COPYRIGHT :

©2023 TACTICAL ELECTRONICS AND MILITARY SUPPLY, LLC.

SPEC SHEET :

PRODUCT SPECIFICATIONS AND INFORMATION ARE SUBJECT TO CHANGE WITHOUT NOTICE. SPEC SHEET: TACTICAL ELECTRONICS



SPECIFICATIONS

POLE GRIP DIMENSIONS (METRIC): POWER SUPPLY:	08ft POLE Grip = L 243.21cm x W 8.25cm x D 4.65cm (71.12cm collapsed) 10ft POLE Grip = L 322cm x W 8.25cm x D 4.65cm (93.98cm collapsed) 17ft POLE Grip = L 533cm x W 8.25cm x D 4.65cm (119.38cm collapsed) 17ft Hinged POLE Grip = L 521cm x W 8.25cm x D 4.65cm (88.9cm collapsed) Three CR123 batteries
RUNTIME:	1.5 hours @ -10°C / 2.5 hours @ 21°C / 1.5 hours @ 50°C
HOUSING MATERIAL:	Polycarbonate+PBT (Valox 357U) and 6061-T6 Aluminum
POLE MATERIAL:	High Density Graphite
OPERATING TEMPERATURE:	-4°F to 122°F / -20°C to 50°C
FREQUENCY RANGE:	5 GHz (Worldwide Availability)
WIRELESS ENCRYPTION:	128-bit AES Encryption with WPA2-PSK Authentication
TRANSMISSION DISTANCE:	650ft, Line of Sight / 200m, Line of Sight
COMPATIBLE CAMERA ATTACHMENTS:	CORE Pole Camera / CORE Under Door Camera / CORE Flex Camera
STORAGE MEDIA:	MicroSD Card



CONTACT :

TACTICAL ELECTRONICS P: 833/483/1441 P: 918/249/8326 F: 918/249/8328

WEBSITE : TACTICALELECTRONICS.COM

DOCUMENT :

OFFICIAL SPECIFICATIONS SHEET *PROPRIETARY*

COPYRIGHT :

©2023 TACTICAL ELECTRONICS SUE AND MILITARY SUPPLY, LLC. WIT

SPEC SHEET :

PRODUCT SPECIFICATIONS AND INFORMATION ARE SUBJECT TO CHANGE WITHOUT NOTICE. 2