



SWIFT UNDER DOOR CAMERA

SPEC SHEET: TACTICAL ELECTRONICS

ELITE CAMERA SYSTEMS



IDENTIFICATION:



FEATURES:

- + **INSERTION PANEL:** 0.26in insertion panel thickness
- + **CAMERAS:** Available in a 1, 2, or 4 camera layout
- + **TOGGLE:** Toggle video between (up to) 4 camera views
- + **LOW-LIGHT VIDEO:** Color low-light sensitive sensor
- + **ILLUMINATION:** Adjustable IR high-intensity LEDs
- + **HARDWIRE:** Hardwire for RF-restricted environments
- + **LCD STATUS SCREEN:** View system status information
- + **BACKLIT BUTTONS:** View push buttons in low light



WIRELESS VIDEO

5GHz real-time Wi-Fi video transmission



ATAK | MANET

Connect real-time video via USB & Ethernet



ENCRYPTED VIDEO

AES encrypted Wi-Fi video streaming



SD RECORDING

Automatic recording to a 32GB MicroSD card



TOGGLE VIDEO

Toggle between four separate camera views



ADJUSTABLE LEDS

Adjustable high-intensity LEDs (0-100%)



SWIFT DEPLOYMENT

Power ON & deploy in under 15 seconds



LOW LIGHT SENSOR

Most sensitive 0.25in sensor on the market

DESCRIPTION:

The SWIFT Under Door Camera is a size, weight, and power optimized Under Door Camera that is compact enough to fit within a Double M4 Mag Pouch. Featuring up to four individual cameras located within a 0.26in thick insertion panel, the SWIFT Under Door Camera provides viewing in four directions inside a room: forward, upward/backward, left, and right. Each viewing direction is supplemented with covert 950nm Infrared LED illumination for both low-light & no-light environments.

The SWIFT Under Door Camera is equipped with a Tactical Accessory Port (TAP) which provides USB and Ethernet connectivity as well as an auxiliary 12VDC power input. The integrated USB and Ethernet ports and on-board 5GHz Wi-Fi allow for video to be streamed to any Tactical Electronics' Monitors, the TE View mobile app or ATAK on Android devices, or MANET radios. All SWIFT products offer Stand-By Mode to help preserve battery life and provide a quick return to video within 10 seconds.

TACTICAL ELECTRONICS

DOCUMENT:

SPECIFICATIONS SHEET
OFFICIAL | PROPRIETARY

COPYRIGHT:

© 2022 TACTICAL ELECTRONICS
AND MILITARY SUPPLY, LLC.

NOTICE: PRODUCT INFORMATION &
SPECIFICATIONS ARE SUBJECT TO
CHANGE WITHOUT NOTICE.

1

WEBSITE: TACTICALELECTRONICS.COM

EMAIL: GOVSALES@TACTICALELECTRONICS.COM

PHONE: (+1) 833 / 483 / 1441 • (+1) 918 / 249 / 8326



SWIFT UNDER DOOR CAMERA

SPEC SHEET: TACTICAL ELECTRONICS

ELITE CAMERA SYSTEMS



SPECIFICATIONS:

WEIGHT:	14oz	0.4kg
DIMENSIONS:	L 8.75in x W 2.75in x H 1.45in	L 22.2cm x W 7.0cm x H 3.7cm
INSERTION PANEL THICKNESS:	0.260in	6.6mm
POWER SUPPLY:	Two x CR123 batteries	
RUNTIME:	Up to 60 minutes	
HOUSING MATERIAL:	HDPE / 6061-T6 Aluminum	
OPERATING TEMPERATURE:	-4°F to 122°F / -20°C to 50°C	
RECORDING CAPACITY & MEDIA:	32GB MicroSD Card	
TRANSMISSION DISTANCE:	Line of Sight (LOS) = up to 500ft / 150m	
WIRELESS ENCRYPTION:	128-bit AES Encryption with WPA2-PSK Authentication	
FREQUENCY RANGE:	5GHz (Worldwide Availability)	
HARDWARE COMMUNICATION:	Compatible integration with: ATAK / MANET / Android mobile device	
HARDWARE DATA TRANSFER:	High-speed Ethernet and USB transfer capable	
HARDWARE CONNECTION:	Push/pull Tactical ODU port and connector	
CAMERA SENSOR:	4 x 0.25in CMOS Color Digital Image Sensor	
CAMERA RESOLUTION:	640 x 480px @ 30fps	
CAMERA LIGHT SENSITIVITY:	16V/lux-sec	
ILLUMINATION:	4 x 950nm IR LEDs (adjustable toggle: 0%, 50%, 100%)	

TACTICAL ELECTRONICS

DOCUMENT:

SPECIFICATIONS SHEET
OFFICIAL I PROPRIETARY

COPYRIGHT:

© 2022 TACTICAL ELECTRONICS
AND MILITARY SUPPLY, LLC.

NOTICE: PRODUCT INFORMATION &
SPECIFICATIONS ARE SUBJECT TO
CHANGE WITHOUT NOTICE.

2

WEBSITE: TACTICALELECTRONICS.COM

EMAIL: GOVSALES@TACTICALELECTRONICS.COM

PHONE: (+1) 833 / 483 / 1441 • (+1) 918 / 249 / 8326