



SWIFT UNDER DOOR CAMERA

SPEC SHEET: TACTICAL ELECTRONICS

ELITE CAMERA SYSTEMS



IDENTIFICATION:



FEATURES:

- + **INSERTION PANEL:** 0.26in insertion panel thickness
- + **CAMERAS:** Available in a 1, 2, or 4 camera layout
- + **TOGGLE:** Toggle video between (up to) 4 camera views
- + **LOW-LIGHT VIDEO:** Color low-light sensitive sensor
- + **ILLUMINATION:** Adjustable IR high-intensity LEDs
- + **HARDWIRE:** Hardwire for RF-restricted environments
- + **LCD STATUS SCREEN:** View system status information
- + **BACKLIT BUTTONS:** View push buttons in low light

WIRELESS VIDEO
5GHz real-time Wi-Fi video transmission

ATAK | MANET
Connect real-time video via USB & Ethernet

ENCRYPTED VIDEO
AES encrypted Wi-Fi video streaming

SD RECORDING
Automatic recording to a 32GB MicroSD card

DESCRIPTION:

The SWIFT Under Door Camera is a size, weight, and power optimized Under Door Camera that is compact enough to fit within a Double M4 Mag Pouch. Featuring up to four individual cameras located within a 0.26in thick insertion panel, the SWIFT Under Door Camera provides viewing in four directions inside a room: forward, upward/backward, left, and right. Each viewing direction is supplemented with covert 950nm Infrared LED illumination for both low-light & no-light environments.

The SWIFT Under Door Camera is equipped with a Tactical Accessory Port (TAP) which provides USB and Ethernet connectivity as well as an auxiliary 12VDC power input. The integrated USB and Ethernet ports and on-board 5GHz Wi-Fi allow for video to be streamed to any Tactical Electronics' Monitors, the TE View mobile app or ATAK on Android devices, or MANET radios. All SWIFT products offer Stand-By Mode to help preserve battery life and provide a quick return to video within 10 seconds.

TACTICAL ELECTRONICS	DOCUMENT:	COPYRIGHT:	NOTICE: PRODUCT INFORMATION & SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.	1	
	SPECIFICATIONS SHEET OFFICIAL PROPRIETARY	©2021 TACTICAL ELECTRONICS AND MILITARY SUPPLY, LLC.			
WEBSITE:	TACTICALELECTRONICS.COM	EMAIL:	GOVSALES@TACTICALELECTRONICS.COM	PHONE:	866 / 541 / 7996 • +1 918 / 249 / 8326



SWIFT UNDER DOOR CAMERA

SPEC SHEET: TACTICAL ELECTRONICS

ELITE CAMERA SYSTEMS



SPECIFICATIONS:

WEIGHT:	14oz / 0.4kg
DIMENSIONS:	L 8.75in x W 2.75in x H 1.45in
DIMENSIONS (METRIC):	L 22.2cm x W 7.0cm x H 3.7cm
INSERTION PANEL THICKNESS:	0.260in / 6.6mm
POWER SUPPLY:	Two x CR123 batteries
RUNTIME:	Up to 60 minutes
HOUSING MATERIAL:	HDPE / 6061-T6 Aluminum
OPERATING TEMPERATURE:	-4°F to 122°F / -20°C to 50°C
RECORDING CAPACITY & MEDIA:	32GB MicroSD Card
TRANSMISSION DISTANCE:	Line of Sight (LOS) = up to 500ft / 150m
WIRELESS ENCRYPTION:	128-bit AES Encryption with WPA2-PSK Authentication
FREQUENCY RANGE:	5GHz (Worldwide Availability)
HARDWARE COMMUNICATION:	Compatible integration with: ATAK / MANET / Android mobile device
HARDWARE DATA TRANSFER:	High-speed Ethernet and USB transfer capable
HARDWARE CONNECTION:	Push/pull Tactical ODU port and connector
CAMERA SENSOR:	4 x 0.25in CMOS Color Digital Image Sensor
CAMERA RESOLUTION:	640 x 480px @ 30fps
CAMERA LIGHT SENSITIVITY:	16V/lux-sec
ILLUMINATION:	4 x 950nm IR LEDs (adjustable toggle: 0%, 50%, 100%)

TACTICAL ELECTRONICS

DOCUMENT:

SPECIFICATIONS SHEET
OFFICIAL I PROPRIETARY

COPYRIGHT:

©2021 TACTICAL ELECTRONICS
AND MILITARY SUPPLY, LLC.

NOTICE: PRODUCT INFORMATION
& SPECIFICATIONS ARE SUBJECT
TO CHANGE WITHOUT NOTICE.

2

WEBSITE: TACTICALELECTRONICS.COM

EMAIL: GOVSALES@TACTICALELECTRONICS.COM

PHONE: 866 / 541 / 7996 • +1 918 / 249 / 8326